

BASIC VI 600-2200 STL



- Human Interface Device (HID) supported
- Multi-purpose button (single-click, double-click or hold to control different functions)
- Equipped with Boost and Buck AVR to stabilize output voltage
- Auto dimming Screen



Model
dependent



Type E
Outlets

Type F
Outlets

Type G
Outlets

The PowerWalker Basic VI STL series is designed to answer the essential market needs. This Line Interactive UPS will protect your load from power failures and voltage disturbances, while remaining affordable and compact. It is equipped with a USB port with HID support allowing easy and immediate communication with any O/S.

Additionally, this series offers an advanced auto-dimming LCD panel with a smart multi-functional button (a single click will illuminate the LCD panel, a double click will mute the alarm and a long-press will control the output).

General Features	Values				
Power Capacity	600VA/ 360W	800VA/ 480W	1000VA/ 600W	1500VA/ 900W	2200VA/ 1320W
Output Power Factor	0.60				
LINE Mode Full Load	95.3%	96.7%	96.8%	95.8%	95.7%
Input Specifications	Values				
Input Voltage Range	162-290 VAC				
Frequency (Synchronized Range)	50Hz or 60Hz				
Input Type	CEE 7/7 or IEC C14 ^{UK}				
Output Specifications	Values				
Nominal Output Voltage	230 VAC				
Frequency (Battery Mode)	+/-1Hz				
Outlets	Type F or Type E (2) - Type G (3)			Type F, Type E or Type G (4)	
Battery Specifications	Values				
Batteries	1 x 12V/ 7Ah	1 x 12V/ 7.2Ah	1 x 12V/ 9Ah	2 x 12V/ 7,2Ah	2 x 12V/ 9Ah
DC Voltage	1 x 12V			2 x 12V	
Recharge Time	8h to 90%				
Half Load Backup Time	5 min		5.5 min	7.5 min	3.9 min
Transfer Time [AC to Battery]	4 ms				