



VFI 1000-3000 AT

- Human Interface Device (HID) supported
- Easy to connect Battery Packs
- Wide input voltage range for all environments
- It supports AC generators
- Includes an Intelligent Slot

Type E
OutletsType F
OutletsType G
Outlets

PowerWalker VFI 1000-3000 AT is an Online UPS with double conversion technology designed to safeguard your mission-critical equipment. Despite its professional application, the VFI AT series is easy to operate and comes inside a compact and economic package.

Rather uniquely among Online UPS, the VFI AT series features outlet sockets for Type F, Type E and Type G plugs. This broadens its usability and allows for different types of application. Multiple optional accessories such as external battery packs and communication cards, enhance the functionality of the UPS and allow for a greater backup time.

General Features	Values		
Power Capacity	1000VA/ 900W	2000VA/ 1800W	3000VA/ 2700W
Output Power Factor	0.90		
LINE Mode Full Load	88.0 %	90.0%	91.0%
Input Specifications	Values		
Input Voltage Range	160-300 VAC	190-300 VAC	
Frequency (Synchronized Range)	40Hz - 70Hz		
Input Type	CEE 7/7, IEC C14 ^{UK} , or IEC C20 ^{UK}		
Output Specifications	Values		
Nominal Output Voltage	208/220/230/240 VAC		
Voltage Regulation	+/- 1%		
Frequency (Battery Mode)	+/-0.5Hz		
Outlets (Model dependent)	Type F or Type E (3), or Type G (2)	Type F or Type E (4), or Type G (3)	
Battery Specifications	Values		
Batteries	2 x 12V/ 9Ah	4 x 12V/ 9Ah	6 x 12V/ 9Ah
DC Voltage	2 x 12V	4 x 12V	6 x 12V
Recharge Time	4h to 90%		
Full Load Backup Time	3.5 min	4	3.5 min
Half Load Backup Time	11 min	11 min	11 min
Transfer Time [AC to Battery]	0		